

# **B150708 Base station communication error**



## Overview

---

Check communication settings, cable and station number. Verify that the devices exist and that their addresses are within a valid range for the connected controller. If you cannot identify it, please read the error code displayed on HMI screen (Fig. 1) and contact our service personnel. We will tell you the next step, where the point is and . I am using delta HMI model DOP-B07E411 with Siemens PLC S7-300, Everything is perfect program is uploading and downloading properly but after some time it will show communication error COM 2 STATION 2: COMMUNICATION ERROR B. The meaning of error messages from the controller shown by the driver. Trimble recommends that you use the Trimble Access software to restart or configure base and rover receivers.

## B150708 Base station communication error

---



### Troubleshooting. Worth Data LT7002H, B5001, B5021, LT7001

If the Terminal displays the " Waiting on Host Prompt " message, the host program is not communicating with the Base Station. There is no radio problem, because the Base Station has already

### [What Does "Device Connection Problem" Mean and How to Resolve It](#)

The app error "Device Connection Problem" occurs whenever the SimpliSafe(R) Mobile App cannot reach your Base Station. This can happen if the Base Station is not connected to its Wi-Fi or cellular



### [Troubleshooting base station setup and static measurement problems](#)

This section describes some possible station setup and static measurement issues, possible causes, and how to solve them. Trimble recommends that you use the Trimble Access software to restart or

### TD-SCDMA/HSDPA Base Station Troubleshooting Guide

Hook up to the frequency reference system (Point "B") for carrier frequency errors. The goal of these measurements is to increase data rate and capacity by accurate power settings, ensuring low out-of





### **DELTA PLC Communication Error solution**

Delta PLC Communication Easy to learn PLC-Motor and OIL pump control (Programmable Logic Controller)-5

### **Delta HMI Communication error**

- Ensure that your communication cable separate from your power wiring. - If the problem still persists, then try lowering the communication baud rate for each device.



### **Troubleshooting**

The meaning of error messages from the controller shown by the driver. Communication fails. Check communication settings, cable and station number. The driver received an unexpected

### **Delta HMI Communication Error List , Error Codes**

Explore the Delta HMI communication error list, including codes 3 and 6, for effective troubleshooting and support.



### [BTS Configuration Error Analysis , PDF , Base Station , Electronic](#)

The alarms include issues with radio network recovery, base station connections, configurations, services, synchronization, and hardware. Most of the alarms provide shared supply information or

### **Updating base station firmware via Bluetooth**

The easiest way to update base station firmware is wirelessly via Bluetooth. Make sure your headset is connected to your PC during the update.



## Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://bartstudio.biz>